
GENIUS2D 12V 2A



Auto | Marine | RV | Powersport | Lawn & Garden

NOCO 2D BATTERY CHARGER + MAINTAINER



CHARGE FULLY DRAINED BATTERIES.

ATVs, Lawn Mowers, Motorcycles, Cars, Trucks, Boats, RVs, Tractors, Equipment, And More.

Introducing the GENIUS2D, one of our most powerful, highest-performing, energy-efficient, and compact chargers yet. The GENIUS2D is a 2-amp direct-mount battery charger and battery maintainer engineered to be securely mounted near the battery. It is designed for all types of 12-volt lead-acid batteries, including flooded, gel, AGM and other maintenance-free batteries.



DIRECT MOUNT.

Weather-resistant on-board charger, built to survive harsh conditions, like engine compartments. Simply plug into a standard extension cord when parked.



CHARGE.

Fully charge batteries on cars, boats, equipment, and more. Works with most lead acid batteries.



MAINTAIN.

Extend the life of your battery.

Optimize performance without overcharging. Safely leave connected indefinitely.

24/7

WORRY-FREE.

Provides all-season, all-weather charging for a healthy battery. Leave plugged in 24/7 with no worries of overcharging. Automatically returns to its last selected mode.



WHAT'S IN THE BOX.

NOCO° Patented Technology

Patented: visit no.co/patents




Technical Specifications			
Input Voltage AC:	120-240 VAC, 50-60Hz	Chemistry:	Wet, Gel, MF, CA, EFB, AGM
Working Volatge AC:	90-264 VAC, 50-60Hz	Charging Current:	2000mA (12V)
Power:	28W Max	Charging Voltage:	Various
Low-Voltage Detection:	1V	Battery Capacity:	Up to 40Ah, Maintains All Battery Sizes
Back Current Drain:	<0.5mA	Housing Protection:	IP65
Ambient Temperature:	-20°C to +60°C, -4°F to +140°F	Dimensions (LxWxH):	5.0 x 2.3 x 1.5 Inches
Charger Type:	Smart Charger	Unit Weight:	0.50 lbs
Type of Batteries:	12V	Cooling:	Natural Convection

Charging Times	(for reference, results may vary)	
Battery Size	Approx. Charge Time in Hours 12V	
8Ah	2	
12Ah	3	
24Ah	6	
40Ah	10	

WHAT'S IN THE BOX.

- · GENIUS2D Smart Charger
- Mounting Bracket Self-tapping Screws (2)
- Secure Velcro Strap
- User Guide & Warranty Information



Retail Packaging:

Dimensions: 5.00"x2.30"x1.50" Weight: 0.50 lbs UPC: 0-46221-18013-8

Inner Carton:

Dimensions: 6.77"x4.09"x4.53" Weight: 1.26 lbs

Master Carton:

Dimensions: 17.24"x14.25"x9.84" Weight: 21.65 lbs Quantity: 16 UCC: 10046221180135

Units Per Pallet:

NA - 480 Units International - 384 Units



BC

CONFORMS TO UL STD. UL1236 CERTIFIED TO CSA STD. C22.2 No.107.2

NOCO

30339 Diamond Parkway, #102 Glenwillow, OH 44139 | USA 1.800.456.6626



