3Ah NLP9



**INSANE PERFORMANCE. LITHIUM POWERSPORT BATTERY.™** 

MORE POWER. **MORE STARTS.** LONGER LIFE.

# DYNAMIC BMS.

Equipped with an auto-enabled, advanced battery management system that provides maximum protection, performance, and bi-directional cell equalization for long-lasting stability. No BMS reset needed.

#### **ACTIVE PROTECTION.**

Protects against over-charge, extreme-heat, short-circuit, over-discharge, extreme-cold, and over-current.

## SHOCK ABSORPTION.

Designed with a custom rubber dampening base and foam inserts to extend the life of the battery and keep connections secure.



30339 Diamond Parkway, #102 Glenwillow, OH 44139 | USA 1.800.456.6626

no.co



#### UNIVERSAL MOUNTING.

Modular spacers can be added to alter the size and allow the battery to be safely and securely mounted. A removable mounting block allows the battery to fit more applications. The threaded insert enables direct-mounting for additional

Removable Mounting Block Hex Screw M6-1x20mm Threaded Insert M6-1 Thread Size.



#### FEMALE.





SIDE.





# **MULTI-CONNECTION TERMINALS.**

Equipped with premium IP66 waterproof copper PCB plates. NLP Terminals can be mounted from the front, side, or top, and can be removed altogether depending on the application.



#### RAPID RECHARGE.

Use the Lithium mode on a Genius charger to fully recharge an NLP battery in minutes. See Genius models and charging times below.

### **COMPATABLE SIZES.**

**BCI SIZES YUASA SIZES ETX SIZES** 


BTX7A-BS BTX9-BS YTX7A-BS BTR9-BS YTX9-BS



NLP9 Battery 12.5mm Spacer

# WHAT'S IN THE BOX 3.4" 3.8" NOCO LITHIUM 叴 (87mm) NOCO . ITHIUM 5.9" LxWxH Maximum. LxWxH Minimum. 5.9" x 3.4" x 3.8" (149mm x 87mm x 96mm) 5.9" x 3.4" x 4.3" (149mm x 87mm x 108.5mm)





RECHARGE TIME	ΛE
GENIUS1	180 Minutes
GENIUS2	90 Minutes
GENIUS5	36 Minutes
GENIUS10	N/A

# **TECHNICAL SPECIFICATIONS**

BCI SIZE:	9		
CHEMISTRY:	Lithium Iron Phosphate (LiFePO4)		
NOMINAL Voltage:	12.8		
AMP-HOURS:	3		
WATT-HOURS (WH):	38.4		
STARTING Current:	400		
CHARGING Voltage (V):	14.6V		
CHARGING Current (A):	9A (Max)		
OPERATING TEMPERATURE:	-20°C to 60°C		
CHARGING TEMPERATURE:	-10°C to 50°C		
STORAGE Temperature:	-20°C to 60°C		
WEIGHT:	2.29 lbs (1.03 kg)		
VOLUMETRICS:	Retail Packaging: Dimensions: 6.18" x 4.84" x 4.77" Weight: 3.17 lbs UPC: 0-46221-19008-3	Master Carton: Dimensions: 13.50" x 6.18" x 10.63" Weight: 15.93 lbs Quantities Quantities Quantities	

**Inner Carton:** 

Dimensions: 6.02" x 4.37" x 5.04"



30339 Diamond Parkway, #102 Glenwillow, OH 44139 | USA 1.800.456.6626

no.co



Quantity: 6 UCC: 10046221190080

Units Per Pallet: 324 Units